



1050 Burke Street, Buhl, Id. 83316 | Phone: 208.543.5351 | Cell: 208.280.6686

## Endura Aluminum Gooseneck Stock & Stock/Combo Trailers



7Ft., 7Ft. 6In., & 8Ft. 2In. INSIDE WIDTH Endura Gooseneck Trailers

### STANDARD EQUIPMENT

Call for pricing and availability.

- |  |   |
|--|---|
| 10 Yr. Warranty  | Single 10K spring loaded drop leg jack          |
| Gooseneck w/ tapered nose  | Flat floor w/ traction surface                  |
| Double wall sliding gate w/ slam latch (2 gates in 26' and longer) | 62" truck clearance                             |
| Double wall sliding rear gate w/ posi- latch                       | Graphics package                                |
| Rubber rollers on sliding gates                                    | Conspicuity tape                                |
| Padlock securable gates  | Heavy duty wiring harness                       |
| Double wall smooth extruded sidewall                               | Enclosed brake wiring                           |
| GN compartment fold down gate                                      | Safety chains                                   |
| 37" wide escape door   | Quick change pigtail, 7-way plug                |
| 52" high solid sides on 6' 8" tall / 60" on 7'4" Tall              | Breakaway battery w/ charger & LED indicator    |
| Adjustable GN hitch height   | LED lights                                      |
| 2-5/16" coupler  | Dome light                                      |
| Full length running boards (Except 8' 2" wide trailer)             | Rubber torsion axle w/ spindle lube 8-bolt hubs |
| One piece roof   | 7K axles w/ 12" x 2" electric brakes            |
| Rear rubber bumper   | Spare tire and wheel for standard axle          |
| Spare tire rack  | Wrap around latch rear gate                     |

Due to product changes standard features are subject to change without prior notice.

## 7 Ft. Inside Width

### 6' 8" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
16ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,735
18ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,860
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,985
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,110
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,235
26ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,540
28ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,665
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,290
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,415
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,540

### 7' 4" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
16ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,835
18ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,970
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,100
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,235
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,365
26ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,680
28ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,815
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,445
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,580
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,710

## 7ft. 6in. Inside Width

### 6' 8" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
16ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,860
18ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,990
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,120
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,250
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,380
26ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,700
28ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,330
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,460
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,590
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,720

### 7' 4" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
16ft.	2-7K	ST235/85R16 LRE	14,500lb.	3,960
18ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,100
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,235
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,375
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,510
26ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,840
28ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,480
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,615
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,755
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,890

## 8ft. 2in Inside Width

### 6' 8" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,440
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,575
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,710
26ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,545
28ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,680
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,815
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,950
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	6,085

### 7' 4" tall Trailer

Floor Length	Axle	Tire Size	GVWR 65 MPH	Approx Trailer Weight (lbs.)
20ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,555
22ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,700
24ft.	2-7K	ST235/85R16 LRE	14,500lb.	4,840
26ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,685
28ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,830
30ft.	3-7K	ST235/85R16 LRE	14,500lb.	5,970
32ft.	3-7K	ST235/85R16 LRE	14,500lb.	6,115
34ft.	3-7K	ST235/85R16 LRE	14,500lb.	6,255